

## PCU-3 Pull Cord Unit Series

## One Pull Can Be Life-Saving



Wireless Pull Cord Unit PCU-3 Series can be quickly installed in any accessible indoor locations for the user to pull for emergency help. When pulled, this wireless device will trigger an alarm, which will be sent by its connected medical alarm to the monitoring center or care personnel. PCU-3's intuitive design is very user-friendly to ensure users know how to use it without further learning.

The wall-mounted or ceiling-mounted PCU-3 can be life-saving when the user does not wear a personal trigger. It gives the user an extra means to raise an alarm and therefore increases chances of rescue. PCU-3 requires very low maintenance and low battery consumption, its functions of automatic low battery reporting and 24-hour supervision prevent operational irregularities and strengthen protection for the user.

The PCU-3 F1 models, which adopt Climax's cutting-edge F1 technology to deliver extensive RF communication range, can be flexibly deployed across large or complex premises. Compatible with Climax's F1 control panels, the PCU-3-F1 also features fast signal transmission and an even longer battery life.

### Features

- White cord with a loop for pulling
- For indoor installation
- Wall-mounted or ceiling-mounted
- Extensive RF technology accelerates the speed of signal transmission and boosts communication range (PCU-3-F1 only)
- Low battery consumption
- Requires low maintenance
- 24-hour supervision transmissions
- Low battery detection
- LED indicator
- Wireless for easy installation

### Specifications

#### PCU-3-F1

Frequency	868MHz / 433MHz
Power Source	3V, CR2 Lithium battery x 1
Battery Life	10 years*
Cord Length	17.5 cm
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	81.2mm x 81.5mm x 43.5mm

\* Note: Actual battery life may vary with product settings, operating environment and usage.

## PCU-3 Pull Cord Unit Series

### Specifications

#### PCU-3

Frequency	869MHz
Power Source	3V, CR2 Lithium battery x 1
Battery Life	5 years*
Cord Length	17.5 cm
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	81.2mm x 81.5mm x 39.1mm

\* Note: Actual battery life may vary with product settings, operating environment and usage.

### Ordering Information

---

**PCU-3-F1** Pull Cord Unit, compatible with Climax's F1 Control Panel and extensive RF range

**PCU-3** Pull Cord Unit, compatible with Climax's Control Panel and gateways