

Temperature Sensor TS-9

TS-9 is temperature wireless sensor device. It reports and transmits temperature condition to the Control Panel every half an hour (30 minutes) to the Host Master Base computer Station LCD, displays the magnitude of the ACTUAL vicinity temperatures.



Features:

- Excellent stability with high sensitivity
- Detects temperature from -10° to 50°C
- Periodic transmissions at intervals of 30 minutes. If no transmission is received, a sensor **out-of-order** fault message will be generated.
- Compact & slim design
- Low Battery detection
- Powered by pre-inserted **Lithium** battery for easy Installation
- LED: Transmission Indicator

Specifications:

- Power: Lithium 1/2 AA batteries x 1 (pre-inserted)
- Battery life: 3.5 years or over¹
- Radio frequency available: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- Range: 433 MHz or 868.35 MHz: over 200 meters in open space
868.6375 MHz: over 300 meters in open space
- Operating temperature: -10° to 50°C
- Humidity: up to 95% non-condensing
- Dimensions: 103 X 31 X x 21 mm

* Note¹: Battery life is calculated at an average of 50 activations per day.



Climax Technology Co., Ltd.
Website: <http://www.climax.com.tw>
Email: sales@climax.com.tw