

## PB-15 Panic Button

## Innovative Communication, Cost-Effective Protection



- Long battery life
- Extensive RF range
- Fast signal transmission
- Classy design

The PB-15 Series provides fixed panic buttons that allow the user to press for help in emergencies. In an urgent situation such as a fall, acute medical problem, fire or burglary, the user can quickly identify the PB-15's big red button and activate the device to report an emergency to monitoring personnel. When transmitting alarm signals, the PB-15 flashes its LED to indicate to the user that alarm reporting is in progress.

The PB-15-F1 model, which adopts Climax's cutting-edge F1 technology to deliver extensive radio frequency (RF) communication range, can be conveniently deployed across large buildings or compounds to provide emergency help. The PB-15-F1 also features fast signal transmission and an extraordinary battery lifespan of 22 years. With the superior advantages of the F1 technology, the PB-15-F1 stands out as a highly cost-effective life safety solution indispensable to a comprehensive emergency alert system.

The classy design of the wall-mounted PB-15 Series blends pleasurably into any environment. This panic button series is waterproof to IPX4 standard and can be installed in easily accessible locations on residential premises.

### Features

- Long battery life
- Extensive RF communication range (PB-15-F1)
- Fast signal transmission (PB-15-F1)
- Compatible with Climax's F1 control panels (PB-15-F1)
- Compatible with Climax's standard control panels (PB-15)
- Classy design
- Big red button for quick identification and activation
- LED indicates the transmission of alarm signals
- Transmits supervisory and low battery signals to the control panel
- IPX4 water resistant rating

## PB-15 Panic Button

### Specifications

#### PB-15-F1

Power source	CR2 3V lithium battery x 1
Battery life*	22 years
Available frequencies	868.6375MHz/433MHz
Operating temperature	-10°C to +45°C
Operating humidity	Up to 85% non-condensing
Dimensions	74 mm x 45.8 mm x 22 mm

#### PB-15

Power source	CR2 3V lithium battery x 1
Battery life*	5 years
Available frequencies	868.35MHz
Operating temperature	-10°C to +45°C
Operating humidity	Up to 85% non-condensing
Dimensions	74 mm x 45.8 mm x 22 mm

\*Note: Battery life varies by use and configuration.

### Ordering Information

<b>PB-15-F1</b>	Long RF range and compatibility with Climax's F1 control panels
<b>PB-15</b>	Compatibility with Climax's standard control panels